BeStar 波 速	SPECIFICATION FOR ULTRASONIC SENSOR		
	TOTAL PAGE	09	www.bestarsensor.com ROHS

Customer		Model Name	BPU1640IOAH12
Customer P/N		Product No.	100902
Date	31. Jul. 2012	Issue No.	BS/TEU01.302C
Page	01 of 09	Issue Date	2012/07/31

Approval:

1.Applications
2.Features
3.Technical terms
4.Drawing
5.Beam Pattern
6.Test Circuit
7.Reliability Test
8.Caution
9.Caution in use
10.Note
11.Packing
12.History change record

Drawn by	Checked by	Approved by	Customer approved
祁小柯	邹东平	李红元	

BESTAR SENSORTECH CO.,LTD
Room 706.No.178. YuLong South Road,Zhonglou district,ChangZhou, JiangSuProvince,P.R.China
Tel: +86 519 88990131 ***Fax:*** +86 519 88990133
E-mail:li@bestarsensor.com ***http://www.bestarsensor.com***

BPU1640IOAH12



1.Applications

Burglar alarms , Range finds , Automatic doors , Remote control.

2.Features

2.1)Open structure and dual use.
2.2) Compact and light weight.
2.3) High sensitivity and sound pressure.
2.4) Less power consumption.
2.5) High reliability.

3.Technical terms


No.	Item	Unit	Specification
1.	Construction		Open Structure
2.	Using Method		Dual Use
3.	Frequency	KHz	40±1K Hz
4.	Sound Pressure Level	dB	min.110dB (10V/30cm)
5.	Sensitivity	dB	min. -65dB /V/ μbar
6.	Capacitance	pF	2500pF±25% at 1KHz
7.	Directivity	°	50deg
8.	Operating Tem.Range	℃	-40 to +85℃
9.	Storage Tem.Range	℃	-40 to +85℃
10.	Detectable Range	m	0.7...18m
11.	Maximum Input Voltage	Vp-p	60Vp-p
12.	Net weight	g	2.32g/pcs
12.	Housing Material		Aluminium


This print and information there in are proprietary to Bestar Sensortech Co., Ltd. and shall not be used in whole or in part without its written content


Rev.	Date	Drawn	Note			
C	12.07.31	祁小柯		Date:	2012.07.31	BPU1640IOAH12
B	10.11.19	祁小柯		Drawn by:	祁小柯	
A	08.09.03	耿亚		Checked by:	邹东平	Ultrasonic Sensor
				Approved by:	李红元	

BPU1640IOAH12

4.Drawing







unit:mm

This print and information there in are proprietary to Bestar Sensortech Co., Ltd. and shall not be used in whole or in part without its written content

Rev.	Date	Drawn	Note		
C	12.07.31	祁小柯		Date:	2012.07.31
B	10.11.19	祁小柯		Drawn by:	祁小柯
A	08.09.03	耿亚		Checked by:	邹东平
				Approved by:	李红元

BESTAR SENSORTECH CO.,LTD
www.bestarsensor.com li@bestarsensor.com

BPU1640IOAH12


Ultrasonic Sensor

DRG NO: BS/TEU01.302C


文件号：BS/ODTE045B

BPU1640IOAH12

5. Beam Pattem



SPL-Freq.Characteristics




Sensitivity-Freq.Characteristics

This print and information there in are proprietary to Bestar Sensortech Co., Ltd. and shall not be used in whole or in part without its written content


Rev.	Date	Drawn	Note			
C	12.07.31	祁小柯		Date:	2012.07.31	BPU1640IOAH12
B	10.11.19	祁小柯		Drawn by:	祁小柯	
A	08.09.03	耿亚		Checked by:	邹东平	Ultrasonic Sensor
				Approved by:	李红元	

BPU1640IOAH12



Directivity in Overall Sensitivity

6.Test circuit



OSC. :Oscillator
F.C :Frequency Counter
U.S :Ultrasonic Sensor
S.C.M:Standard Cappacitor Microphone
Amp. :Ampifier

This print and information there in are proprietary to Bestar Sensortech Co., Ltd. and shall not be used in whole or in part without its written content

Rev.	Date	Drawn	Note			
C	12.07.31	祁小柯		Date:	2012.07.31	BPU1640IOAH12
B	10.11.19	祁小柯		Drawn by:	祁小柯	
A	08.09.03	耿亚		Checked by:	邹东平	Ultrasonic Sensor
				Approved by:	李红元	

BPU1640IOAH12

7.Reliability Test

7.1	High temp.life test	
	Temperature	+85±3 ℃
	Duration	100hrs
7.2	Low temp.life test	
	Temperature	-40±3 ℃
	Duration	100hrs
7.3	Heat Cycle Test	
	Temperature	+85±3 ℃ 1hour
		-40±3 ℃ 1hour
	Cycles	10cycles
7.4	Humidity Test	
	Temperature	+60±2 ℃
	Relative Humidity	90~95%
	Duration	100hrs

Tests above should be measured after leaving normal temperature for24hrs.

7.5	Vibration Test	
	Vibration Frequency	10~55Hz
	Sweep Period	1min
	Amplitude(peak to peak)	1.5mm
	Direction	3(x.y&z)
	Time	2hours/direction
7.6	Shock test	
	Acceleration	sine 100G
	Direction	3directions
	Shock time	3 time/directions
7.7	Drop test	
	Height	1m on concrete floor
	Times	2times

7.8 Connector soldering check:

Immersing terminal up to 1mm below base in soldering bath at 260 ℃ 10 seconds

Notice:

The variation of the S.P.L or the sensitivity at 40KHz is within 3dB compared with initial figures at 25 ℃ in 24 hours after above test condition.

This print and information there in are proprietary to Bestar Sensortech Co., Ltd. and shall not be used in whole or in part without its written content

Rev.	Date	Drawn	Note		
C	12.07.31	祁小柯		Date:	2012.07.31
B	10.11.19	祁小柯		Drawn by:	祁小柯
A	08.09.03	耿亚		Checked by:	邹东平
				Approved by:	李红元

BESTAR SENSORTECH CO.,LTD www.bestarsensor.com li@bestarsensor.com

BPU1640IOAH12

Ultrasonic Sensor

DRG NO: BS/TEU01.302C

文件号：BS/ODTE045B

8. Caution

8.1 Limitation of Applications

Please contact us before using our product for the applications listed below which require especially high reliability for the prevention of defects which might directly cause damage to the third party's life,body or property.

1) Aircraft equipment
2) Aerospace equipment
3) Undersea equipment
4) Power plant control equipment
5) Medical equipment
6) Transportation equipment (vehicles,train,ships,etc.)
7) Traffic signal equipment
8) Disaster prevention/crime prevention equipment
9) Data-processing equipment
10) Application of similar complexity and/or reliability requirement to the applications listed in the above

8.2 Fail -safe

Be sure to provide an appropriate fail-sate function on your product to prevent a second damage that may be caused by the abnormal function or the failure of our product

9. Caution in use

1) Please avoid applying an excessive stress to the transducer because it might be damaged.
2) The transducer may generate surge voltage by mechanical or thermal shock. Care should be taken to protect from it in designing your application circuit.
3) Please do not applying DC voltage to the transducer.
4) Please do not use the transducer in water.
5) The piece of sensor may be damaged by force pressure from back of sensor.
6) Please do not use the sensor without painting on the surface.
7)Please well evaluate the painting and electrical characteristic for your coating.


10. Note

1) Please make sure that your product has been evaluated in view of your specifications with our product being mounted to your product.
2) You are requested not to use our product deviating from the agreed specifications.
3) We consider it not to appropriate to include any terms and conditions with regard to the business transaction in the product specifications,drawings or other technical documents. Therefore, of your technical documents as above include such terms and conditions such as warranty clause, product liability clause,or intellectual property infringement liability clause, they will be deemed to be invalid

This print and information there in are proprietary to Bestar Sensortech Co., Ltd. and shall not be used in whole or in part without its written content

BPU1640IOAH12

11.Packing



1)50 pcs/tray
2)40 trays/carton
3)2000 pcs/carton in total
4)carton size: 500X280X340m m

This print and information there in are proprietary to Bestar Sensortech Co., Ltd. and shall not be used in whole or in part without its written content

Rev.	Date	Drawn	Note		
C	12.07.31	祁小柯		Date:	2012.07.31
B	10.11.19	祁小柯		Drawn by:	祁小柯
A	08.09.03	耿亚		Checked by:	邹东平
				Approved by:	李红元

BESTAR SENSORTECH CO.,LTD
www.bestarsensor.com li@bestarsensor.com

BPU1640IOAH12

Ultrasonic Sensor

DRG NO: BS/TEU01.302C

文件号：BS/QDTE045B

BPU1640IOAH12

12. History change record

version No.	Change Items		Date	Drawn	Approved
	Before	After			
A			08.09.03	耿亚	李红元
B	Water proof type 、Test circuit	Open type 、Test circuit	10.11.19	祁小柯	李红元
C	10±0.5	9±1	12.07.31	祁小柯	李红元

This print and information there in are proprietary to Bestar Sensortech Co., Ltd. and shall not be used in whole or in part without its written content

Rev.	Date	Drawn	Note		
C	12.07.31	祁小柯		Date:	2012.07.31
B	10.11.19	祁小柯		Drawn by:	祁小柯
A	08.09.03	耿亚		Checked by:	邹东平
				Approved by:	李红元

BESTAR SENSORTECH CO.,LTD www.bestarsensor.com li@bestarsensor.com

BPU1640IOAH12

Ultrasonic Sensor

DRG NO: BS/TEU01.302C

文件号：BS/QDTE045B